

ATMe

The finest haze on the market...



... just got better.

Nice work.

ATMOSPHERE series

TECHNICAL DATA

- Single high output
- 100% Duty Cycle
- Variable haze output
- Last operation mode memory
- Recordable failure / anomaly logs
- Firmware upgradable

- Automatic Purging System[™] (APS[™])
- Maximum Gas pressure input: 4.14 Bar (60 PSI)
- 4 standard USITT DMX512 channels, XLR-5, 1 input, 1 output.
- RDM compliant device.
- USB 2.0 Link connector (control)

ATMe

		ATIVIC
Fluid type (M.S.D.S. available on request)		MDG Neutral Fluid
Consumption	(per hour at 1.38 bar/20 psi)	55 ml (1.62 oz / 0.0145 US gallon)
	(per hour at 2.76 bar/40 psi)	110 ml (3.24 oz / 0.0290 US gallon)
Gas type		Industrial grade CO ₂ or N ₂ only
Consumption	(per hour at 1.38 bar/20 psi)	0,18 kg (0.4 lb)
	(per hour at 2.76 bar/40 psi)	0,36 kg (0.79 lb)
Control		4-button LCD user interface,
		DMX XLR-5 connectors, RDM compliant device
Total running time	(per hour at 1.38 bar/20 psi)	46 hours
	(per hour at 2.76 bar/40 psi)	23 hours
Reservoir capacity		2,5 L (0.66 US gallon)
Automatic Purging System (APS)		Standard feature
Haze colour		Pure white
Partical size		0,5 - 0,7 micron
Warm-up time (maximum)		8 minutes
Operating voltage		100-250 VAC, 50/60 Hz single phase
Power consumption		715 W
Noise emission (at 1 m/3.3 ft)		45.4 dB (A)
Dimension	Length	68,5 cm (27")
	Width	18 cm (7")
	Height	30 cm (12")
Weight		16.8 kg (37 lb)
Shipping weight (without flight case)		22 kg (48.5 lb)
Shipping weight (with flight case)		30.5 kg (67 lb)
Approval		C €, CSA and UL
-		

FLUID

MDG Neutral Fluid

Safe, non-toxic fog fluid, withthe longest hanging time. Available in 4 L (1 US gallon), 5 L (Europe only), 20 L (5.3 US gallon), 205 L (55 US galon) and 1000 L (264 US gallon) sizes.



ACCESSORIES

Flight case

Durable for safe and easy transport





10301 av. Pelletier, Montréal, Québec, Canada H1H 3R2 T (514) 272-6040 1-800-663-3020 F (514) 722-3229 info@mdgfog.com www.mdgfog.com